

SL



PEERLESS[®]
electric-électrique

INCEP|TION[®]
PEERLESS CANADA

CONCEPT

The SL is a **LED luminaire** for **recessed** in an exposed flat 15/16” T-grid ceiling. Standard lens is #12 clear prismatic acrylic diffuser. Steel frame retained with pin hinges and positive slide latches with locking thumb screws. “Protective” fixture alternative is available, with tamper resistant mounting screws and polycarbonate lens. Plaster frame kit available, consult factory. Ideal for commercial environments.

CERTIFICATION

Approved to UL1598 and CSA C22.2 No. 250 standards**

Suitable for damp locations.



*LED Five (5) year limited warranty. ***Complies with Buy American Act.

**Operating temperature: -20°C to +35°C / -4°F to +95 °F, consult factory for operating temperatures outside the listed range.


Specifications are subject to change. Please confirm latest specifications prior to placing order.



STRUCTURE

Body
Steel frame retained with pin hinges and positive slide latches with locking thumb screws. "Protective" fixture alternative is available, with tamper resistant mounting screws and polycarbonate lens.

Advanced Optics
Standard lens is #12 clear prismatic acrylic diffuser. Other shielding options available.

**LED Driver**

1% Dimming (0-10V).
Emergency driver available.
DALI (Digital Addressable Lighting Interface), Lutron EcoSystem LED, and other drivers available, consult factory.

MOUNTING



RECESSED






CLEAN DESIGN

SL is a luminaire designed for simplicity and effectiveness.




PHOTOMETRIC DATA



SL-22G-30-35K

0°-180° —
90°-270° —

Available in 3000K, 3500K, 4000K and 5000K preset CCT



OR

AS TUNABLE WHITE






COLOR

Standard finish is matte white polyester baked powder coat enamel. Matte grey and black available. Custom colours available.




DIMENSIONS

SIZE	L	W	H
14G	49.05"	13.00"	4.90"
22G	23.80"	23.80"	4.90"
24G	47.65"	23.80"	4.90"



ORDERING INFORMATION

SL							
FIXTURE	SIZE	LUMENS	CCT	SHIELDING	CAPTIVE LENS	*OPTION*	DRIVER
SL = Steel Frame. Latches.	14G = 1' X 4' T-Bar Ceiling	30 = 3000lm	30K = 3000K	12 = Clear Prismatic Acrylic	CK = Standard Screws	W = Water Resistant Gasketed	MV = Standard 120V-277V 1% Dimming (0-10V)
		36 = 3600lm	35K = 3500K	12R = Clear Prismatic Acrylic Reversed (Gasketed)	CT = Tamper Resistant Screws		347 = Standard 347V Dimming (0-10V)
		40 = 4000lm	40K = 4000K	12P = Clear Prismatic Polycarbonate 0.125in THK			EM = Emergency Driver
	22G = 2' X 2' T-Bar Ceiling	52 = 5200lm	50K = 5000K	12PR = Clear Prismatic Polycarbonate 0.125in THK Reversed (Gasketed)			X = DALI, Lutron EcoSystem LED, and other drivers available, consult factory
		30 = 3000lm	TW = Tunable White				
		32 = 3200lm	*Other CCT, RGB (Red, Green, Blue LEDs), DM (dim to warm) available, consult factory				
	24G = 2' X 4' T-Bar Ceiling	35 = 3500lm					
		40 = 4000lm					
		46 = 4600lm					
		40 = 4000lm					
		48 = 4800lm					
		64 = 6400lm					
		82 = 8200lm					
		90 = 9000lm					



2900 Loyalist St.
Cornwall, ON
K6H 6C8
T: 613.510.1268
F: 613.510.1268

info@peerless-electric.com
Peerless-Electric.com