

PEERLUX®  
SERIES

# SDL-SP50

 **PEERLESS**  
electric-électrique

INCE|T|O|N<sup>®</sup>  
PEERLESS CANADA

# CONCEPT

The SDL-SP50 is a **LED luminaire** for **recessed** installation in an exposed flat 15/16" T-grid ceiling. Lateral perforated steel baskets with opal overlays. Rigid one-piece body constructed from code gauge steel. Air handling available, consult factory. Plaster frame kit available, consult factory. Ideal for commercial office spaces, schools and retail spaces.

## CERTIFICATION

Approved to UL1598 and CSA C22.2 No. 250 standards\*\*


Suitable for damp locations.



\*LED Five (5) year limited warranty. \*\*\*Complies with Buy American Act.  
 \*\*Operating temperature: -20°C to +35°C / -4°F to +95 °F, consult factory for operating temperatures outside the listed range.  
 Specifications are subject to change. Please confirm latest specifications prior to placing order.



## STRUCTURE



## MOUNTING






## ADVANCED OPTICS

Frosted acrylic improves LED visual performance and eliminates glare.



## PHOTOMETRIC DATA



SDL-SP50-22G-40-35K

0°-180° █  
 90°-270° █



## TUNABLE WHITE FUNCTION OPTIONS

Available in 3000K, 3500K, 4000K and 5000K



## COLOR

Standard finish is matte white polyester baked powder coat enamel. Matte grey and black available. Custom colours available.



## DIMENSIONS


### DIMENSIONS - METRIC

SIZE	L	W	H
600G	600mm	600mm	83mm
612G	600mm	1200mm	83mm

### DIMENSIONS - IMPERIAL

SIZE	L	W	H
22G	23.95"	23.90"	3.25"
24G	47.95"	23.90"	3.25"


\*other sizes available, consult factory



## ORDERING INFORMATION

SDL	SP50				
FIXTURE	SHIELDING	SIZE* T-Bar Ceiling	LUMENS	CCT	DRIVER
SDL	SP50 = Side Perforated Basket at 50%	22G = 2' x 2'	25 = 2500lm 32 = 3200lm 40 = 4000lm 55 = 5500lm	30K = 3000K 35K = 3500K 40K = 4000K 50K = 5000K  TW = Tunable White	MV = Standard 120V-277V 1% Dimming (0-10V)  347 = Standard 347V Dimming (0-10V)  EM = Emergency Driver
		24G = 2' x 4'	44 = 4400lm 48 = 4800lm 60 = 6000lm 66 = 6600lm	*Other CCT, RGB (Red, Green, Blue LEDs), DM (dim to warm) available, consult factory	X = DALI, Lutron EcoSystem LED, and other drivers available, consult factory

\*other sizes on request



OFFICE:

255-438 Isabey  
St-Laurent, QC H4T 1V3  
T: 514.595.1671  
F: 514.595.4411

PRODUCTION:

2900 Loyalist Str.  
Cornwall, ON K6H 6C8  
T: 613.510.1268  
F: 613.510.1268

[info@peerless-electric.com](mailto:info@peerless-electric.com)  
[Peerless-Electric.com](http://Peerless-Electric.com)