

PROJECT:  
CAT.NO:  
NOTES:

DATE:  
TYPE:  
VOLTS:

**ARCLUX**  
SERIES

# TB

T-Bar



RECESSED

## GENERAL DESCRIPTION

**LED luminaire** for **recessed** installation, replaces a 15/16 t-bar.

The integrated design allows to create seamless continuous or discontinuous linear lighting arrangements that perfectly blend with the ceiling, consult factory.

Ideal for architecture and commercial environments.



2019-05-09

## CONSTRUCTION

Aluminum extrusion.

## FINISH

High gloss white polyester baked powder coat enamel.



## CERTIFICATION

Approved to UL1598 and CSA C22.2 No. 250 standards\*\*  
Suitable for damp locations.



\*LED Five (5) year limited warranty.  
\*\*Normal temperature: -20 degrees Celsius to +25 degrees Celsius.  
\*\*\*Not all available products are DLC qualified. Check the DLC Qualified Products List at [designlights.org](http://designlights.org) to confirm which versions are qualified.

## SHIELDING

Snap-in frosted acrylic lens.

## ELECTRICAL

3000K 3500K 4000K 5000K

120V - 277V

L80 performance at 60,000 hours minimum. 80 CRI Standard.  
Other dimming options, lumen options, 90CRI and lengths available.  
Consult factory.

Specifications are subject to change.  
Please confirm latest specifications prior to placing order.

## ORDERING INFORMATION

TB	LENGTH	WATTAGE	CCT	MV DRIVER
	2 = 2ft	10W = 10 Watts	30K = 3000K 35K = 3500K 40K = 4000K 50K = 5000K	MV = Standard 120V-277V Dimming (0-10V)  *emergency driver available, consult factory
	4 = 4ft	20W = 20 Watts		

PROJECT:  
CAT.NO:  
NOTES:

DATE:  
TYPE:  
VOLTS:

**ARCLUX**<sup>®</sup>  
SERIES

# TB

## DIMENSIONS

2019-05-09


SIZE	L	W	H
2ft	24.00"	0.95"	1.95"
4ft	48.00"	0.95"	1.95"

## SIZES

2FT



H-W-H



4FT



H-W-H

