



TB-LI



PEERLESS[®]
electric-électrique

INCEP|TION[®]
PEERLESS CANADA

CONCEPT

The TB-LI is a **LED luminaire** for **recessed** installation. Easy push-in T-bar grill panel lights. Aluminum body and optical polycarbonate diffuser. Provides a distribution of 115°. Widely used in offices, residences, factories, super markets, hotels, restaurants, and schools.

CERTIFICATION

Approved to UL1598 and CSA C22.2 No. 250 standards**

Suitable for damp locations.



*LED Five (5) year limited warranty.

**Operating temperature: -20°C to +35°C / -4°F to +95 °F, consult factory for operating temperatures outside the listed range.

***Not all available products are DLC qualified. View DLC Qualified Products List at designlights.org to confirm which versions are qualified.

Specifications are subject to change. Please confirm latest specifications prior to placing order.

STRUCTURE

LED Driver

1% Dimming (0-10V).
Emergency driver available.
DALI (Digital Addressable
Lighting Interface), Lutron
EcoSystem LED, and other
drivers available, consult factory.

Body

Aluminum extrusion
t-grid bracket.

Advanced Optics

Polycarbonate diffuser.



SELECTABLE CCT OPTIONS

Available in 3500K, 4000K, and 5000K.



DIMENSIONS

SIZE	L	W	H
1 x 4	47.48" (1206mm)	11.87" (301.5mm)	0.945" (24mm)
2 x 2	23.74" (603mm)	23.74" (603mm)	0.945" (24mm)
2 x 4	47.48" (1206mm)	23.74" (603mm)	0.945" (24mm)



ORDERING INFORMATION

TB-LI				O	MV3
FIXTURE	SIZE	WATTAGE	CCT	DIFFUSER	DRIVER
TB-LI = Lay-in T-Bar Grid	14G = 1 x 4 Grid	V35W = (25-30-35)	V40K = Selectable CCT 35K-40K-50K	O = Opal	MV3 = 120-347
	22G = 2 x 2 Grid				
	24G = 2 x 4 Grid	V45W = (35-40-45)			



2900 Loyalist St.
Cornwall,
ON K6H 6C8
T: 613.510.1268
F: 613.510.1268

info@peerless-electric.com
Peerless-Electric.com