

GENERAL DESCRIPTION

LED luminaire for surface or suspended installation with field adjustable aircraft cables or v-links for mounting chain. Rounded extruded ribbed frosted acrylic lens. Ideal for commercial environments or residential environments. Row mounting available, consult factory.

CERTIFICATION

Approved to UL1598 and CSA C22.2 No. 250 standards**
Suitable for damp locations.



*LED Five (5) year limited warranty. ***Complies with Buy American Act.
**Operating temperature: -20°C to +35°C / -4°F to +95 °F, consult factory for operating temperatures outside the listed range.
Specifications are subject to change. Please confirm latest specifications prior to placing order.



ELECTRICAL

3000K 3500K 4000K 5000K

120V - 277V 347V


*TW (Tunable White), other CCT, RGB (Red, Green, Blue LEDs), DM (dim to warm) available, consult factory.
L80 performance at 60,000 hours minimum.
80 CRI Standard. Other dimming options, lumen options, 90CRI and lengths available, consult factory.

FINISH

Standard finish is glossy white polyester baked powder coat enamel.




PHOTOMETRIC DATA



DIMENSIONS


SIZE	L	W	H
4FT	48.00"	13.50"	6.25"

MOUNTING / CROSS SECTION




ORDERING INFORMATION

ITS	4	1ACF =			W			
FIXTURE	LENGTH	STYLE	LUMENS	CCT	FINISH	CONTROLS *OPTIONAL*	MOUNTING *OPTIONAL*	DRIVER
ITS = Industrial LED Strip	4 = 4ft	1ACF = 1 Acrylic Frosted Lens	32 = 3200lm 40 = 4000lm 46 = 4600lm 60 = 6000lm 80 = 8000lm 100 = 10000lm *other lumens available	30K = 3000K 35K = 3000K 40K = 4000K 50K = 5000K	GLOSSY W = White	OC = On/Off Occupancy Control O5 = 100%-50% Hi/Low Occupancy Control Click here for suggested control options	A4-C1 = 48in Aircraft Cable & 5ft Cord A5-C2 = 60in Aircraft Cable & 6ft Cord A8-C4 = 96in Aircraft Cable & 9ft Cord A12-C7 = 144in Aircraft Cable & 13ft Cord	MV = Standard 120V-277V, 1% Dimming (0-10V) 347 = Standard 347V Dimming (0-10V) EM = Emergency Driver X = DALI, Lutron EcoSystem LED, and other drivers available, consult factory



DIMENSIONS

SIZE	L	W	H	MTG L	MTG W
4FT	48.00"	13.50"	6.25"	40.00"	3.12"



SHIELDING

Rounded extruded frosted acrylic, lineal ribbed on inside or polycarbonate frosted lens.

CONSTRUCTION

Rigid one-piece body constructed from code gauge steel.

FINISH

Standard finish is glossy white polyester baked powder coat enamel.



LED LIGHT ENGINE

Mounted on internal high reflectance white painted reflector.

LED DRIVER

1% Dimming (0-10V). Emergency driver available. DALI (Digital Addressable Lighting Interface), Lutron EcoSystem LED, and other drivers available, consult factory.

ELECTRICAL

3000K 3500K 4000K 5000K

120V - 277V 347V

*TW (Tunable White), other CCT, RGB (Red, Green, Blue LEDs), DM (dim to warm) available, consult factory. L80 performance at 60,000 hours minimum. 80 CRI Standard. Other dimming options, lumen options, 90CRI and lengths available, consult factory.

CERTIFICATION


Approved to UL1598 and CSA C22.2 No. 250 standards** Suitable for damp locations.




*LED Five (5) year limited warranty. ***Complies with Buy American Act. **Operating temperature: -20°C to +35°C / -4°F to +95 °F, consult factory for operating temperatures outside the listed range.

MOUNTING / CROSS SECTION

Surface installation on ceiling or **suspended** installation with field adjustable aircraft cables or v-links for mounting chain.




SURFACE



SUSPENDED

PHOTOMETRIC DATA



ITS-4-1ACF-50-40K

0°-180° █
90°-270° █